



CRC SUPER GASKET REMOVER

Ref. : 10937

1. GENERAL DESCRIPTION

Powerful stripper.

CRC Super Gasket Remover is a blend of powerful solvents, formulated for a fast removal of gasket cement, paints, adhesives and sealants.

2. FEATURES

- Powerful stripper for paints, varnishes and lacquers.
- Softens and eases removal of conventional and formed in-place gaskets, gasket cements and sealants.
- Loosens carbon deposits.
- Dissolves tar, greases, dried oils, adhesives, resinous deposits, etc.
- Clings very well to all surfaces, even vertical surfaces.
- All coating layers (that have to be removed) are softened and easy to remove by a jet of water.
- Can be used on all surfaces; metal, glass, wood, stone, etc.
- Avoids accidental and costly damage caused by excessive scraping.

3. APPLICATIONS

Removal of:

- Gasket residues on:
 - cylinder heads
 - crankcases
 - gearboxes
 - water pump flanges, ...
- Carbon deposits on:
 - valve seats
 - cylinder heads
 - metal engine components, ...
- Paints, coatings and varnishes on:
 - metals
 - stone
 - hard surfaces, ...
- Mastics
- Putties
- Sealants
- Adhesives



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC SUPER GASKET REMOVER

Ref. : 10937

4. DIRECTIONS

- Mask painted surfaces from over spray. Wear eye protection and non-porous (polyvinylalcohol rubber) gloves.
- Aerosol: Shake well and spray from a distance of about 20 cm a thick layer.
- Bulk: Stir the product before use, apply a thick film with a brush.
- Allow product to work for about 10 minutes.
- Remove the residues by rinsing it with water, if necessary, remove them first with a stiff bristled brush or putty knife.
- Repeat application if necessary.
- Clean treated surface with a solvent cleaner (CRC Quickleen) to remove waxy product film.
- Test before use on plastics or rubber. Do not use on energised equipment.
- Use only in well ventilated areas.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: viscous opaque liquid
Specific gravity @ 20°C	: 1,24
Boiling range (solvents)	: 40°C - 210°C
Freezing point	: < -20°C
Flash point (closed cup)	: non flammable mixture
pH	: neutral
Viscosity	: 80 mPa.s
Kauri-Butanol value (solvents)	: ± 130

6. PACKAGING

aerosol : 12 x 500 ml
bulk : 4 x 5 l

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10937 03 1199 02
Date : 18 november 2004



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

